



KEYED NOTES		
MARK	QTY	DESCRIPTION
1	1	CAST IN CITY OF HOUSTON RING AND COVER
2	1	TOP SECTION
3	1	RISER AS REQ'D
4	1	BASIN SECTION
5	1	THINWALL KNOCKOUTS
6	1	NAMEPLATE MFG: ParkUSA 888-611-PARK WWW.PARKUSA.COM MODEL: COHH2I-2

NOTE: BASE SIZE ADJUSTABLE FROM 30"X60" TO 60"X60".



## SPECIFICATIONS

CONCRETE : CLASS II CONCRETE WITH OF DESIGN STRENGTH OF 4500 PSI AT 28 DAYS. UNIT IS OF MONOLITHIC CONSTRUCTION AT FLOOR AND FIRST STAGE OF WALL WITH SECTIONAL RISER TO REQUIRED DEPTH. RATED FOR H-20 LOADING.

REINFORCEMENT: GRADE 60 REINFORCED. NO. 4 STEEL REBAR TO CONFORM TO ASTM A615 ON REQUIRED CENTERS OR EQUAL.

C.I. CASTINGS: CAST IRON FRAMES AND GRATES ARE MANUFACTURED OF GREY CAST IRON CONFORMING TO ASTM A48-76 CLASS 30.

© ParkUSA. ALL RIGHTS RESERVED.

PROJECT: .				
CUSTOMER: .				
ENGINEER: .				
ORDER #:		PROJ #:		
DATE:		LOCATION:		
www.parkusa.com 888-611-PARK				
TYPE-H2 CURB INLET CITY OF HOUSTON - MODEL COHH2I-2				
PM	PC	DRN	ENG	DWG. NO.
DATE	01/2019			COHH2I-2
				REV.