



KEYED NOTES		
MARK	QTY	DESCRIPTION
1	2	30"x17" HD CAST IRON FRAME & GRATE
2	1	TOP SECTION
3	1	RISER SECTION
4	1	BASIN SECTION
5	4	30" DIAMETER KNOCK OUT (WILL ACCOMMODATE UP TO 24" RCP)
6	1	NAMEPLATE MFG: ParkUSA 888-611-PARK WWW.PARKUSA.COM DATE MANUFACTURED MODEL: BGI-1

**SPECIFICATIONS**

**CONCRETE :** Class I/II concrete with of design strength of 4500 PSI at 28 days. Unit is of monolithic construction at floor and first stage of wall with sectional riser to required depth. Rated for H-20 Loading.

**REINFORCEMENT:** Grade 60 reinforced with steel rebar to conform to ASTM A615 on required centers or equal.

**C.I. CASTINGS:** Cast iron frames and grates are manufactured of grey cast iron conforming to ASTM A48-76 Class 30.



TYPE-B GRATE INLET  
MODEL BGI-1

PM	PC	DRN	ENG	DWG. NO.	REV.
				BGI-1	A
DATE					

PLOTTED ON 4/19/2024 2:54 PM BY Vu. Kate. C:\Users\vu\Desktop\file replacement website\BGI-1

© ParkUSA. ALL RIGHTS RESERVED.